

Digital Receipt

This receipt acknowledges that Turnitin received your paper. Below you will find the receipt information regarding your submission.

The first page of your submissions is displayed below.

Submission author: Mohamad Jahja

For writers Assignment title:

On nonlinear optical constants of ... Submission title:

> File name: On_Nonlinear_optical_constants_o..

12.64K File size:

Page count: 2

Word count: 552

2,775 Character count:

Submission date: 10-Jul-2019 01:57 AM (UTC-0500)

Submission ID: 1150695108

International Symposium on Modern Optics and Its Applications - 2011

On nonlinear optical constants of polystyrene

Mohamad Jahja Universitas Negeri Gorontalo, Jurusan Fisika, Jl. Jend. Sudirman no. 6, Gorontalo 96128,Indonesia

mj@ung.ac.id

Polystyrene (PS) has found known applications in integrated optics as passive waveguide [1, 2, and 3] and also as active waveguide, with organic dopant like rhodamine 6G [4]. It is transparent in the visible and NIR range and also has an ultrallow waveguide loss of 0.1 dB/cm and small birefringence of 4.7x10⁷ [1, 2, and 3]. Hu et al. [5, 6 and 7] demonstrated an all-optical-switching process in a polystyrene photonic crystal (PC). These reports have stimulated researches on nonlinear optical properties of PS. We performed nonlinear prism coupling to measure the n; and c₃ of PS waveguide at 532 nm, and change of the refractive index and absorption coefficient induced by varying the applied intensity. The absorption coefficient and refractive index values at corresponding average guided intensities. Alleuse of n, and α, which were derived from the linear fitting curves in absorption coefficient and refractive index values at corresponding average guided intensities. Values of n_0 and α_2 which were derived from the linear fitting curves in Fig. 1a and b are considered as maximum possible values at 532 nm. Hu et.al. [5] reported that the shift of 5 nm was induced by 18.7 GW/cm² which means $\Delta n_0 = 50/20 = 0.011$ which corresponds to $n_0 = 5.9 \cdot 10^{13}$ 10 10 W. This value is 23 times of the maximum n_2 value of ours. The reason is not fully understood yet. The M_0 of their PS is almost 8 times higher than our PS. These facts are observed already as M_∞ dependence on $\chi^{(3)}$, which are reported elsewhere [8 and 9]. But such a strong dependence on molecular weight is unlikely. We assume that the high repetition rate (76 MHz) of the laser system used by Hu, et. al. [6] could give rise to additional of thermal nonlinearities.

- References
 [1] T.P. Sosnowski, Opt. Commun. 4 (1972) 408.
 [2] W. M. Prest Jr. and D. J. Luca. "The origin of the optical anisotropy of solvent cast polymeric films", J. Appl. Phys. 50 (1979) 6067.
 [3] W. M. Prest Jr. and D. J. Luca, "The alignment of polymers during the solvent-coating process", J. Appl. Phys. 51 (1980) 5170.
 [4] R. Ulrich and H. P. Weber, "Solution-Deposited Thin Films as Passive and Active Light-Guides", App. Optics 11 (1972) 428.
 [5] X. Y. Hu, Q. H. Gong, Y. H. Liu, B. Cheng and D. Zhang," All-optical switching of defect mode in two-dimensional nonlinear organic photonic crystals", Appl. Phys. Lett. 87 (2005) 231111.
 [6] X. Y. Hu, P. Jiang, C. Y. Ding, H. Yang and Q. H. Gong, "Picosecond and low-

On nonlinear optical constants of polystyrene

by Mohamad Jahja

Submission date: 10-Jul-2019 01:57 AM (UTC-0500)

Submission ID: 1150695108

File name: On_Nonlinear_optical_constants_of_polystyrene.pdf (12.64K)

Word count: 552

Character count: 2775

International Symposium on Modern Optics and Its Applications – 2011

On nonlinear optical constants of polystyrene

Mohamad Jahja

Universitas Negeri Gorontalo, Jurusan Fisika, Jl. Jend. Sudirman no. 6, Gorontalo 96128,Indonesia

mj@ung.ac.id

Polystyrene (PS) has found known applications in integrated optics as passive waveguide [1, 2, and 3] and also as active waveguide, with organic dopant like rhodamine 6G [4]. It is transparent in the visible and NIR range and also has an ultralow waveguide loss of 0.1 dB/cm and small birefringence of 4.7x10⁻³ [1, 2, and 3]. Hu et al. [5, 6 and 7] demonstrated an all-optical-switching process in a polystyrene photonic crystal (PC). These reports have stimulated researches on nonlinear optical properties of PS. We performed nonlinear prior coupling to measure the n_2 and α_2 of PS waveguide at 532 nm, and change of the refractive index and absorption coefficient induced by varying the applied intensity. The absorption coefficient and refractive index values at corresponding average guided intensities. Values of n_2 and α_2 which were derived from the linear fitting curves in Fig.1a and b are considered as maximum possible values at 532 nm. Hu et.al. [5] reported that the shift of 5 nm was induced by 18.7 GW/cm² which means $\Delta n_{PS} = 5/(2.220) = 0.011$ which corresponds to $n_2 = 5.9 \cdot 10^{-13}$ cm²/W. This value is 23 times of the maximum n2 value of ours. The reason is not fully understood yet. The Mw of their PS is almost 8 times higher than our PS. These facts are observed already as M_w dependence of $\chi^{(3)}$, which are reported elsewhere [8 and 9]. But such a strong dependence on molecular weight is unlikely. We assume that the high repetition rate (76 MHz) of the laser system used by Hu, et. al. [6] could give rise to additional of thermal nonlinearities.

References

- [1] T.P. Sosnowski, Opt. Commun. 4 (1972) 408.
- [2] W. M. Prest Jr. and D. J. Luca, "The origin of the optical anisotropy of solvent cast polymeric films", J. Appl. Phys. 50 (1979) 6067.
- [3] W. M. Prest Jr. and D. J. Luca, "The alignment of polymers during the solvent-coating process", J. Appl. Phys. 51 (1980) 5170.
- [4] R. Ulrich and H. P. Weber, "Solution-Deposited Thin Films as Passive and Active Light-Guides", App. Optics 11 (1972) 428.
- [5] X. Y. Hu, Q. H. Gong, Y. H. Liu, B. Cheng and D. Zhang," All-optical switching of defect mode in two-dimensional nonlinear organic photonic crystals", Appl. Phys. Lett. 87 (2005) 231111.
- [6] X. Y. Hu, P. Jiang, C. Y. Ding, H. Yang and Q. H. Gong,"Picosecond and low-

International Symposium on Modern Optics and Its Applications - 2011

- power all-optical switching based on an organic photonic bandgap microcavity", nat. photonics 2 (2008) 185.
- [7] Y. Liu, F. Qin, Z.-Y. Wei, Q.-B. Meng, D.-Z. Zhang and Z-Y. Li"10 fs ultrafast all-optical switching in polystyrene nonlinear photonic crystals" App. Phys. Lett. 95 (2009) 131116.
- [8] H. Kishida, K. Hirota, T. Wakabayashi, H. Okamoto, H. Kokubo and T. Yamamoto, "Third-order optical nonlinearity in regio-controlled polythiophene films", Appl. Phys. Lett., 87 (2005) 121902.
- [9] K. Koynov, A. Bahtiar, T. Ahn, R. M. Cordeiro, H.-H. Hörhold and C. Bubeck, "Molecular Weight Dependence of Chain Orientation and Optical Constants of Thin Films of the Conjugated Polymer MEH-PPV", Macromolecules 39 (2006) 8692.

On nonlinear optical constants of polystyrene

ORIGINALITY REPORT

2%

SIMILARITY INDEX

INTERNET SOURCES

PUBLICATIONS

STUDENT PAPERS

PRIMARY SOURCES



MOHAMAD JAHJA. "NONLINEAR OPTICAL WAVEGUIDE SPECTROSCOPY OF POLY(3-BUTYLTHIOPHENE)", Journal of Nonlinear Optical Physics & Materials, 2010

Publication



Submitted to University of Leeds Student Paper

Exclude quotes

Off

On

Exclude matches

Off

Exclude bibliography