# **PROSES TERBIT JURNAL**

### A. LATAR BELAKANG

Publikasi jurnal ini dilakukan dalam rangka penyelesaian studi S3 dan untuk memenuhi syarat terbit artikel menuju tahapan Seminar Hasil dan Promosi Doktor.

Pertimbangan teknis untuk jurnal tujuan adalah:

- 1. Memilih jurnal yang memenuhi syarat yang ditetapkan oleh institusi tempat studi yakni jurnal terindeks Scopus minimal quartil 3 atau (Q3).
- 2. Memilih jurnal yang masa proses muat artikel lebih pendek (pertimbangan waktu tunggu untuk segera selesai studi).
- 3. Memilih jurnal berkategori low cost (pertimbangan biaya karena semester ekstra tanpa Beasiswa lagi).

- B. Tahapan dan Prosedur
  - 1. Mencari informasi person to person yang sudah melakukan publish di suatu jurnal dengan kriteria memenuhi pertimbangan teknis pada bagian A.
  - Pencarian informasi, diperoleh nama jurnal yakni : Jounal Engineering and Applied Scince, (JEAS) dibawah penerbit Asian Research Publishing Network, (ARPN).
  - 3. Menelusuri laman website jurnal ARPN JEAS.
  - 4. Menelusuri kebenaran jurnal dengan:
    - a. Menelusuri peringkat jurnal (H-indeks dan Quartil) di laman SJR,
    - b. Menelusuri data indeks di laman Scopus,
    - c. Apakah jurnal tersebut juga terindeks thomson,
    - d. Apakah jurnal ada di laman journal predator.

Proses penelusuran....

### Hasil Penelusuran laman jurnal Penerbit ARPN.

← → C ▲ Not secure	arpnjournals.com	Q	☆		<b>A</b> 8.	*	•		ø
Home Submit Paper Author Guidelines Publication Fee	ANNOUNCEMENT ARPN has launched a new online international research journal " <u>ARPN Journal of Earth Sciences</u> " since Octobe technology and sciences related to Geology, Mining Engineering, Geo Physics, Geo Science, Geography etc. Rese send their original research articles to ARPN. ARPN requires Editors and Associate Editors for this Journal also. Visit: <u>ARPN Journal of Earth Sciences (JES)</u>	r 2012, This journ archers and stude	al cove nts of l	ers almo M.S., M	ost all Phil a	disciplir and Ph.	nes of D are	engine reques	ering ted to
Our Journals' Frequency IEAS: 24 issues in a year IABS: 12 issues in a year IES: 12 issues in a year Journals Abstracting/ Indexing	ARPN is publishing an online international research journal "Journal of Engineering and Applied Sciences". This sciences. Researchers and students of M.S., M.Phil and Ph.D are requested to send their original research articl published on the Internet. Visit: <u>ARPN Journal of Engineering and Applied Sciences (JEAS)</u> ARPN is publishing an online international research journal "Journal of Agricultural and Biological Science". Research their original research articles to ARPN. All articles after approval from reviewers shall be published on the Internet. Visit: <u>ARPN Journal of Agricultural and Biological Science (JABS)</u>	ournal covers ain les to ARPN. All i ers and students (	nost all articles of M.S.,	discipl after a M.Phil	ines o pprova and P	f engin al from h.D are	eering revie	and a wers sh	ppliec all be
Journal of Computing	The new Issue of the online international research journal "Journal of Agricultural and Biological Science" is now availad Visit: Volume 14 : ARPN Journal of Agricultural and Biological Science The new Issue of the online international research journal "Journal of Engineering and Applied Sciences" is now availad Visit: Volume 15 : ARPN Journal of Engineering and Applied Sciences The new Issue of the online international research journal "Journal of Engineering and Applied Sciences" is now availad Visit: Volume 15 : ARPN Journal of Engineering and Applied Sciences The new Issue of the online international research journal "Journal of Earth Sciences" is now available on the Internet. Visit: Volume 6 : ARPN Journal of Earth Sciences ARPN Journals are also available via libraries of EBSCO Publishing, 10 Estes Street, P.O. Box 682, Ipswich, MA 0193 Phone: +1-978-356-6500 or (800) 653-2726 Ext. 546	ble on the Interne ble on the Internet 8, USA.							

Note: JEAS, JABS, JES adalah 3 jurnal yang tergabung pada Penerbit ARPN

### ..... Hasil Penelusuran laman jurnal ARPN JEAS.

← C ③ www.arp	njournals.com/journals_abstracting_indexing.htm	Q 國 ☆ 🖉
Submit Paper Author Guidelines	ARPN Journals are abstracted/indexed in the following databasis:	
Subscribe to ARPN	DOAJ (Lund University, UK)	DOAL DIRECTORY OF OPEN ACCESS JOURNALS
	SCOPUS (Elsevier, USA)	This title is indexed. in SciVerse Scopus
	EBSCO Publishing (USA)	
	Chemical Abstracts Service (a division of The American Chemical Society, USA)	
	INSPEC (The Institution of Engineering and Technology, England, UK)	Engineering and Technology
	Inture (Henor-Wart University Library Edinburgh, UIC)	intute
	Socolar (China Educational Publications Import and Export Corporation- CEPIEC)	Socol@r
	Open J-Cate (Informatics, India)	J-Gate

Note: Terdapat indeks Scopus untuk di telusuri di laman resmi Scopus

## ..... Hasil Penelusuran laman jurnal ARPN JEAS.



**Note:** Biaya publikasi termasuk low cost dan sesuai dengan isi dompet mahasiswa S3 semester ekstra serta level salari/gaji dosen negeri di Indonesia.

## ..... Hasil Penelusuran laman jurnal ARPN JEAS.



ARPN Journal of Engineering and Applied Sciences

Home

Archive

Submit Paper

**Author Guidelines** 

**Editorial Board** 

### ANNOUNCEMENT

ARPN has launched an online international research journal titled "Journal of Engineering and Applied Sciences". Those researchers, who are interested to publish their research articles online, are requested to send their original research articles to <u>ARPN</u>. The original research work undertaken by students of Master of Science (MS), M. Phil and Ph. D shall be given priority. All articles after approval from reviewers shall be published **Online**.

Visit our site at http://www.arpnjournals.com

E-mail: arpn@arpnjournals.com

- Inconvenience regretted for those who are not researchers and/or not interested.
- N.B.: Please circulate it among your friends and professional colleagues.
- **Note:** Terdapat info prioritas untuk hasil-hasil penelitian studi S2 dan S3 sehingga peluang keterterimaan baik. Aspek waktu tunggu menjadi lebih pendek agar bisa menyelesaikan studi S3 sesegera mungkin.

a. Hasil penelusuran di laman ScimagoJR.

SJR	Scimago Journal & Country Rank					Enter Journal Title: ISSN or P
	Home Jo	ournal Rankings	Country Rankings	Viz Tools	Help	About Us
	ARPN Journ	al of Eng	gineering a	and Ap	plied	Sciences 👌
	Country	Pakistan		1	5	
	Subject Area and Category	Engineering Engineering	g (miscellaneous)		9	
	Publisher	Asian Research	Publishing Network (AF	RPN) HI	ndex	
	Publication type	Journals				
	ISSN	18196608				
	Coverage	2011-ongoing				
	Quartiles : Q3					+

Note: Jurnal berstatus coverage : 2011-ongoing dengan H indeks 15, Q3 (2017).

### ..... Hasil penelusuran di laman ScimagoJR.

SJR Solmage	Journal & Country R	iank						0156504				
	Home	Journal R	ankings	Country Rank	ings	Viz Tools	Help	About Us				
	ARPN Jo	urnal	of Er	ngineer	ing a	and A	pplie	d Scie	ence	es	3	
Country	Pakistan - IIII Si	R Ranking of F	Pakastan	27	1							
Subject Area and Category	Engineering Engineering (m	sceilaneous)		21								
Publisher				HIndex								
Publication type	Journals											
ISSN	18196608											
Coverage	2009, 2011-2020											
Scope	Information not loca	alized										
Quartiles								-	+			

Note: Sekarang status coverage : 2011-2020, H indeks 27 & Kuartil Q2 (2020).

### Statistik Jurnal ARPN Journal of Engineering and Applied Science di laman ScimagoJR (SJR)





Lanjutan Statistik Jurnal ARPN Journal of Engineering and Applied Science di laman ScimagoJR (SJR)

## b. Hasil Penelusuran laman Scopus.

sources					
CiteScore metrics for serials CiteScore metrics from Scopus are comprehensive, transparent, current and free metrics fo browse below to find a source and see associated metrics. Use the annual metrics for repor 2017 metrics with CiteScore Tracker 2017. Be sure to use qualitative as well as the below qu your research impact, and always use more than one metric for the quantitative part.	or serial titles in Scopus. ting, and track the programitative inputs when p	Search or ress of presenting	Documen	Citas ta fiseri 1 yawa 2014 2015 2016	ees = 3038.
Search for a source Browse sources				🛃 Download Scop	us Source List 🔘
Search arpn journal of engineering and applied sciences	×q				
Title () ISSN () Publisher [] Display only Open Access journals ()					
1 source found matching "arpn journal of engineering and applied sciences".					-
1 source found matching "arpn journal of engineering and applied sciences".	① CiteScore	Œ) SJR ∽	© SNIP~	Type	damilters

# **Note:** Jurnal tersebut terindeks di Scopus untuk penelusuran Tahun 2017 bulan April sebelum submit.

### ......Menelusuri data indeks jurnal di laman Scopus.

# Data indeks "Scopus Source List" di Laman Scopus: <u>https://www.scopus.com/home.uri</u> Atau download langsung pada : <u>https://www.elsevier.com/?a=91122</u>

	A	B	С	E	G	H	1	J	K	M	P	AA
4	Sourcerecord ID	Source Title (Medline-sourced journals are indicated f in Green)	Print-ISSN	Active or Inactive	Coverage	Article languag e in	2017 Cite So re	2018 co Cite Sco re	2019 Cite Sco re	Open Access status, i.e., registered in DOAJ and/or ROAD. Status April 2020	Source 1	yTop level: Physical Sciences
3597	22182	Arkivon	15517004	Activo	2000 ongoing	ENG	93	43	43	DOA I/ROAD Open Access	lournal	Physical Sciences
3508	16562	Armod Forces and Society	00053277	Activo	1074 ongoing	ENG	50	51	48	DOMINOAD Open Access	Journal	r nysical ociences
3500	21100912436	Armanian Journal of Mathematics	00333217	Active	2019-ongoing	ENG	2.0	4-1	0 1	DOA I/POAD Open Access	Journal	Physical Sciences
3600	19700170236	Arms and Armour	17/1612/	Active	2010-ongoing	ENG	50.2	53	03	DOADINOAD Open Access	Journal	T hysical ociences
3601	75942	ARN journal : the official journal of the Association of Reha	03623505	Inactive	1975-1980	Ento	0.2	0.0	0.0		Journal	
3602	21100837406	Arnold Mathematical Journal	21996792	Active	2015-ongoing	ENG	0.6	0.9	0.7		Journal	Physical Sciences
3603	21100200825	ARPN Journal of Engineering and Applied Sciences	18196608	Active	2011-ongoing	ENG	0.6	0.9	1.2	DOAJ/ROAD Open Access	Journal	Physical Sciences
3604	5800173395	ARQ	07160852	Active	2007-ongoing	SPA, EN	C0.1	0.1	0.1	DOAJ/ROAD Open Access	Journal	Physical Sciences
3605	21100200407	Arqueologia	03275159	Active	2011-ongoing	ENG, SP	A0.6	0.5	0.6	DOAJ/ROAD Open Access	Journal	
3606	21100201513	Argueologia de la Arguitectura	16952731	Active	2011-ongoing	POR. ITA	0.3	0.3	0.3	DOAJ/ROAD Open Access	Journal	Physical Sciences
3607	21100220374	Arqueologia Iberoamericana	19894104	Active	2012-ongoing	SPA	0.7	9.0	9.1	DOAJ/ROAD Open Access	Journal	and a second second second second
3608	21100212326	Arqueologia Mexicana	01888218	Active	2018-ongoing	20 SPA	0.1	0.1	0.0	State of a state of a state of a state	Journal	
3609	19700182317	Arquiteturarevista	18085741	Active	2010-ongoing	POR	0.1	0.1	0.1		Journal	Physical Sciences
3610	17672	Arquivo Brasileiro de Medicina Veterinaria e Zootecnia	01020935	Active	1996-ongoing	POR	0.5	0.5	0.5	DOAJ/ROAD Open Access	Journal	
3611	33067	Arquivos Brasileiros de Cardiologia	0066782X	Active	1950-ongoing	POR	2.0	2.0	2.4	DOAJ/ROAD Open Access	Journal	
3612	25410	Arquivos Brasileiros de Endocrinologia e Metabologia	00042730	Inactive	2004-2014, 198	30-1986, 196	0-1969			La tot and the state of the	Journal	
3613	26576	Arquivos Brasileiros de Medicina	03650723	Inactive	1983-1999, 196	57-1968, 195	2-1963				Journal	-
3614	13302	Arquivos Brasileiros de Oftalmologia	00042749	Active	2000-ongoing.	19TPOR	1.5	1.8	1.8	DOAJ/ROAD Open Access	Journal	
3615	93325	Arquivos Brasileiros de Pediatria	01045652	Inactive	1997						Journal	
3616	59860	Arquivos Brasileiros de Psicologia	01008692	Active	2009-ongoing,	1982	0.2	0.2	0.1	DOAJ/ROAD Open Access	Journal	
3617	77927	Arquivos da Faculdade de Higiene e Saude Publica da Uni	03652203	Inactive	1963-1966, 198	57-1961					Journal	
3618	4900152208	Arquivos de Biologia e Technologia	03650979	Inactive	1996						Journal	
2040	04000	A T PERCE PLOT AND T	00700005	1 0	1005 1000							

### c. Hasil penelusuran di laman Thomson

http://search.babylor	📥 Google Drive 🚦	Mengapa masuk ke	0	3 Gmail: Email from Go	M https://mail.google.c	G	🛋 Direktorat Jenderal F	🗋 New Tab
-	Clar Analy	<b>ivate</b> tics					Site Search	
	Customer Care	Training						
4	Clarivate Master Journal	List Journal Search						
J	OURNAL SEA	RCH IG Sea Tota es THE FC Journal	rch Te I jour PLLOV s 1-1	Terms: ARPN Irnals found: 1 WING TITLE(S) MATC (of 1)	HED YOUR REQUEST.			
	different styles. with <b>EndN</b>	ote"		> . Þ			FORM	AT FOR PRINT
	endnote.com	> ARPI Month ASIAN TOWN Cover	y ISSI RES ISLA age	URNAL OF AGRICU IN: 1990-6145 PUBL NETWORK-ARP AMABAD, PAKISTAN, 4	LTURAL AND BIOLOG N, OFF 9, QADRI PLZ, NEW 5500	ICAL	. SCIENCE	O SHAZAD

Note: ARPN sebagai penerbit terindeks Thomson khusus jurnal JABS (lihat hal. 3)

## d. Hasil penelusuran di laman jurnal predator.



Note: Nama jurnal dalam kotak merah tidak sama dengan nama jurnal di hal. 3.

Laporan hasil penelusuran ke TIM Promotor untuk mendapat persetujuan dan selanjutnya di cek ke staf Universitas tentang keabsahan jurnal jika di terbitkan di "Journal of Engineering and Applied Science" pada penerbit ARPN.

Tim Promotor dan Staf Pengecekan UNHAS memberikan respon bahwa jurnal yang dituju untuk publikasi adalah valid.

	ARPN Journ	al of Enginee	ring and Applied Sciences
Home Submit Paper Author Guidelines	Submit Paper For online submission of manus size up to 10 MB. If your file an Make sure that the submitted man Please note that the blanks with (	cript papers, pl ze is more tha nuscript is not i ") are essential	ease fill in the following correctly. The online submission system supports file n 10 MB, then please divide your file in parts and send these files one by one. in process of publication anywhere in any conference journal across the globe. , others are optional.
		Name: + E-Mail: * address * Phone: File: Title: * Abstract:	Online Submission System Plih File_Tidak ada he yang diplih Submit

Proses Submit Manuskrip selanjutnya dilakukan pada Tgl 14 April 2017.

### Respon atau jawaban dari Publishing Editor pada Tgl 18 April 2017.

ARPN Journal of Engineering and Applied Sciences arpn@arpnjournals.com via core24.hostingm Apr 18 (4 days ago) to me me -

Dear Sir / Madam,

We would like to inform you that we have received a manuscript titled " Design and performance of a cyclone separator integrated with heat exchanger for smoked fish production " for publication in the ARPN Journal of Engineering and Applied Sciences. Shortly we will send your submitted manuscript to the reviewers. After approval from referees, your paper will be published in the next available Issue of the Journal. Please quote the title of your research paper while making correspondance with us. Please do not send frequent e-mails asking recent status of your paper. We will contact you as and when required. Please note that we are charging a fee for processing of your research article (Article Processing Charge-APC). Thank you very much for your interest in ARPN Journals.

Sincerely yours

Publishing Editor ARPN Journals URL, http://www.arpniournals.com

# Permintaan revisi/perbaikan artikel mengikuti petunjuk penulisan manuskrip

THOR GUIDES	FOR PREPARATION OF MANUSCRIPT	
se follow the follow	ing instructions:	
AGE SETUP		
Margins=> Top	0.7 mich, Bottem: 0.7 mich R: 0.7 mich, Rights 0.7 mich	
Paper=> Port	rait, A4 size (6.27 inch x 11.69 inch)	
Header/Footer=	> 0.4 inch Each	
TTLE OF ARTICLE	Bookman old style, Font size 14	
UTHOR(S) NAME	Times New Roman, Font side 11	
RGANIZATION NA	Times New Roman, Font size 9	
BSTRACT	Times New Roman, Font size 10	
EYWORDS	Times New Roman, Font size 9	
ALL TEXT (Introduc Results	tion, Literature Review, Naterials and Methods and Discussions, Acknowledgement, References etc.)	0
	Times New Roman, Font size 10, Single Spaced, Justify both sides, First Line of all Paragraphs inder No Line Briaks between Paragraphs	vied,
n case of 2 column		
	Column Width: 3.28 lisch Column Späcing: 0.3 inch With equal column width	
HOTOGRAPHS	JPG and GIP format Inserted immediately after the citation in the test	
ABLES	Times New Roman, Font size 10 Inserted immediately after the citation in the text	
ILE FORMAT	M5 Word (.DOC)	

For reference please have a look at:

Volume 5, No. 2 of the Journal of Engineering and Applied Sciences

### Penyelesaian administrasi biaya atau Article Processing Charge (APC) Tgl 6 Mei 2017

ARPN <arpn@arpn/ournals.comto Muhammad + May 6 2017 36 AM

Dear Author,

We have received your email. Thank you very much. We will inform you after receiving of your payment.

With best wishes and regards,

Sincerely yours

Publishing Editor ARPN Journals URL: <u>http://www.arpnjournals.com</u> E-Mail: <u>arpn@arpnjournals.com</u> Please include all previous correspondence when replying to this email.

From: Muhammad Tahir [mailto:muhtahir@ung.ac.id] Sent: Wednesday, May 3, 2017 12:52 PM To: ARPN Journal of Engineering and Applied Sciences Subject: The Payment of APC for ARPN Journal of Engineering and Applied Science

Dear Sir,

I have just finished the payment of article processing charge-APC for my paper entitle "DESIGN AND PERFORMANCE OF A CYCLONE SEPARATOR INTEGRATED WITH HEAT EXCHANGER FOR SMOKED FISH PRODUCTION".

The payment through Direct Payment in Bank for the amount of \$150.00. The process is Interbank between BNI in Indonesia and UBL in Pakistan.

The Remittance Application is as attached below.

Sincerely yours. Muh. Tahir

### Editing dan Proofreading yang diminta dalam proses review paper, tgl 3 Juli 2017



• Revisi paper selesai tgl 5 Juli 2017 utk memenuhi permintaan Publishing Editor

	M Gmail		Q t	ransb	ahasa.	.go@gr	mail.cor	n			×		0	۲		ĵ	UNGma	1
+	Compose		÷	۵	0	Ŧ	Ø	0	Ø,	۲		1	3	7 of 7	<	ż	-	
-				Trans	sBahas	a Goror	ntalo «tra	nsbahas	sa.go@gm	nall.com×		e ju	1 5, 2017, 1	0:37 AM	\$		s 1	
	Inbox	1,084		to me														
*	Starred			XA	Indon	esian •	> E	nglish	• Trans	slate mes	sage			Turn off	for: Ind	lones	ian x	
0	Snoozed			Yth B	apak Ta	hir.												
	Important			Droof	reading	dan ad	ting copy	ico untul	k manuck	rin artikoj	Banak	tolah kamil	kariakan K	ami lam	nirkan	ocros	r aboat	
2	Cont			sebel	um dan	sesudal	n proses (	pengerja	aannya. S	ielain mei	nggunał	an Gramm	arly, artikel	Bapak k	kami ba	ca la	gi	
-	Sent			secar	a manu	al untul r	mengece	k kesala	ihan-kesa	lahan ya	ng mung	gkin terlewa	tkan oleh (	Gramma	rly prem	nium :	service	
				Bersa Moho dilaku Terim	ama ini j in agar i ikan a kasih	uga kam kiranya c telah me	il lampirk lapat mei empercey	an invoid ngkonfin akan Tri	ce tagihar masikan I ansbahas	n biaya di kepada ki a.	an cara ami via e	pembayara email atau s	nnya. sms apabila	ı pemba	yaran te	elah		
				Best	wishes													
				14.5	morroo,													
				-														
				Rega	rds,													
				TRAN	BAHASA													
				Legalia	ad by Min	isteriai Diep	rae of Law:	and Homa	n Rights of (	he Republic	af Indone	eie -						
				Numbe	r, AHU-DO	0964) AH.	01.07 2017											
				Ermail g	transpana	53.90@om	ail.com / Ph	one: +82.8	953 9862 59	76								

### Upaya percepat proses review & revisi paper pada jurnal ARPN JEAS, tgl 12 Juli 2017



....

## Penegasan proses review melalui status paper di website jurnal, tgl 19 Juli 2017

=	M Gmail		Q	arpn@	arpnjo	ournals.	com				×	*	0	٢	***	UN	Grail
+	Compose		÷	۵	0	Ħ	Ê	o	¢,	۲		ł	2	of 17	<	>	<b>.</b> -
	Inbox	1.084	12	ARPN to me	N <arpn< td=""><td>garphjou</td><td>rnals.com</td><td>1&gt;</td><td></td><td></td><td></td><td>J.</td><td>ul 19, 2017,</td><td>6:19 PM</td><td>☆</td><td>*</td><td>5</td></arpn<>	garphjou	rnals.com	1>				J.	ul 19, 2017,	6:19 PM	☆	*	5
*	Starred			Dear	Autho	r,											
Q	Snoozed			Your	paper	is unde	r proces	s. Plea	ase wait!	Please	visit ou	ır websit	e (Status	of upo	oming	pape	rs)
	Important			from	time t	o time.											and the
>	Sent			With	best v	/ishes a	nd rega	rds.									
				Since	erely y	ours											
				Publ	lishing	Editor	÷										
				ARP	N Jour	rnals											1
				URL:	: http:	//www	v.arpnj	ourna	ls.com								
				E-Ma	ail: arp	on@arp	njourn	als.co	m								
				Pleas	se inclu	ide all r	revious	corres	nonden	o when	ranhvir	a to this	licma				

-----

### Permintaan mengirim kembali paper hasil revisi/perbaikan Tgl 28 Agustus 2017

ARPN <arpn@arpnjournals.com> to Tahir + Aug 28, 2017, 1:49 AM

Dear Author,

Would you please send your papers in MS Word FORMAT as an email attachment to ARPN.

With best wishes and regards.

Sincerely yours

Publishing Editor ARPN Journals URL: http://www.arpnjournals.com E-Mail: arpn@arpnjournals.com Please include all previous correspondence when replying to this email.

On Wed, Aug 30, 2017 at 8:50 PM, Muh. Tahir <muhtahir@ung.ac.id> wrote:

Dear Editor,

I send this manuscript after two days of your email because this file was newly rehealing from bad hard disk, sorry for about. This file is written in MS Word Format (DOC and DOCX) as your request and following the instruction of manuscript preparation guided by JEAS.

Sincerely yours,

Muhammad Tahir

...

# Upaya percepat proses terbit paper pada jurnal ARPN JEAS, tgl 23 September 2017

	M Gmail		Q	arpn@	arpnjo	ournals	com				×	*	0	۲		Ū	Grail
+	Compose		÷	٥	0	Ĩ.		C	Ø,	۲		÷	.2	of 17	<	> =	-
*	Inbox Starred	7,084		Muh tō AR	. Tahir	<muhtahi< th=""><th>r@unġ.ac</th><th>.id&gt;</th><th></th><th></th><th></th><td></td><td>Sep 23, 2017,</td><td>5 13 PN</td><td>☆</td><td>*</td><td>1</td></muhtahi<>	r@unġ.ac	.id>					Sep 23, 2017,	5 13 PN	☆	*	1
O A A	Snoozed Important Sent			For the entitle	he final ed:	exam se	ssion of n	ny study	progress	s, I need i	informat	ion abo	ut publishing e	dition pl	an to the	manus	cript
				SMO This i sessi	IGN AN KED FI	ID PERF SH PRO tion is ne	ORMANC DUCTION eded to c	omplete	the requ	isition of	the cere	monial	BATED WITH	e schoo	L My fina	al exam	ж
				) will	be grate	eful for yo	our answe	er and I	want to h	ear from	you soa	n.					
				Since	erely												
				Muha	ammad	Tahir											

# Proses terbit artikel di jurnal ARPN JEAS dalam waktu 6 bulan, tgl 15 November 2017 Laman download artikel adalah :

http://www.arpnjournals.org/jeas/research papers/rp 2017/jeas 1017 6366.pdf

=	M Gmail		Q	arpn@	arpnjo	ournals	com						4	× -	0	٢		ŏ	NGe
+	Compose		÷	۵	0	8		0	¢,	۲		ŧ			5	of 17	\$	>.	<b>-</b> 7
	Inbox	1,084	12	ARP to me	N <arpn< td=""><td>@arpnjo.</td><td>imals.con</td><td>n≥</td><td></td><td></td><td></td><td></td><td></td><td>Ъ</td><td>4ov 15, 2017</td><td>4:15 PN</td><td>1 12</td><td>*</td><td>ŧ</td></arpn<>	@arpnjo.	imals.con	n≥						Ъ	4ov 15, 2017	4:15 PN	1 12	*	ŧ
*	Starred			Dear	Autho	ог,													
G	Snoozed			Pleas	se che	ck,													
	Important			http	. 1)		unale a	en line		-		203.7/	101	7 6966 44	2				
>	Sent			***		<u>v.arpint</u>	urnals.c	<u>ng/19a</u>	IS/TESE8	ircin pap	pers/1p	2017/3	eas 101	/ 0300.00	1				



Dec 5, 201

Dec 5, 2017, 12:21 PM 📩 🖡

to ARPN = Dear ARPN,

Muh. Tahir <muntahir@ung.ac.id>

I very thankful that my research paper entitled Design and Performance of a Cyclone Separator Integrated with Heat Exchanger for Smoked Fish Production has published.

I only ask if the author does not receive an appreciation such as a certificate or any other on their manuscript contribution.

Furthermore, to provide this material of research paper into the worldwide. I want to inform you that this material will be republished in the book format and this will be done by one of the publishing group in Europe. I think this effort is a step to bring my research paper goes to worldwide without a violation of the copyright, that I had not transfer it yet to anyone.

sincere regards, Muhammad Tahir

¢,

www.arpnjournals.com

### DESIGN AND PERFORMANCE OF A CYCLONE SEPARATOR INTEGRATED WITH HEAT EXCHANGER FOR SMOKED FISH PRODUCTION

M. Tahir<sup>1,2</sup>, Mursalim<sup>3</sup>, Salengke<sup>3</sup> and Metusalach<sup>4</sup>

<sup>1</sup>Department of Science & Food Technology, Universitas Negeri Gorontalo, Gorontalo, Indonesia
 <sup>2</sup>Postgraduate School, Universitas Hasanuddin, Makassar, Indonesia
 <sup>3</sup>Department of Agricultural Engineering, Universitas Hasanuddin, Makassar, Indonesia
 <sup>4</sup>Department of Fisheries Science, Universitas Hasanuddin, Makassar, Indonesia
 E-Mail: muhtahir@ung.ac.id

#### ABSTRACT

This paper presents the design and performance characteristics of a cyclone separator used in smoked fish processing. The application of cyclone in smoked fish processing was intended to reduce contaminants such as char, ash, soot, and a fraction of tar with its polycyclic aromatic hydrocarbon (PAH) compound in the smoked fish. These contaminants potentially decrease both product quality and safety of smoked fish. The cyclone used was designed according to high-efficiency Stairmand's cyclone to separate solid particles from the smoke-air stream. A centrifugal blower of the cyclone, which was integrated with a heat exchanger, generated a forced smoke-air stream of the indirect smokehouse. The collection efficiency of the cyclone was 94.7%, which was higher than the prediction of 93.3%. Visual observation found that tar was trapped and sticky at the inside surface of the cyclone and the dust bin. The reduction of these contaminants contributed to the decrease of the PAH compound, which was indicated by low benzo(a)pyrene content (below the maximum level of Turkish food codex for 2.0  $\mu$ g/kg). The total pressure drop of the cyclone was 204 Pa, which was lower than the predicted value of 332 Pa. The ratio of energy consumed to pressure drop for the cyclone separator was 22.6 MJ/Pa.

Keywords: smokehouse, fly ash, collection efficiency, benzo (a) pyrene, solid particles.

#### **INTRODUCTION**

Smokehouse in this study was intended to process fish into processed products with smoke flavour. This method of processing has been known for a long time and had evolved since the beginning of human civilisation. Smoking techniques based on smoke temperature can be divided into cold smoking (12-25 °C), warm smoking (25-45 °C) and hot smoking (40-90 °C) [28]. Principally, smoking process is done by burning biomass materials in a burning chamber which generate smokes. Smokehouses can be grouped into three types based on smoke-air stream; i.e. (1) natural air circulation, (2) air-conditioned or forced air, and (3) continuous. Modifications of these three types can be found anywhere in our surrounding but the trends of the air-conditioned or forced-ventilation smokehouses have largely replaced the natural-air type [1].

Smoke from biomass consists of components such as gases, liquid, and solid particles. Most of the smoke is air with a mixture of small particles of different sizes. The smoke contains mostly particle which diameters less than 2.5  $\mu$ m, with the greatest concentration of < 0.12  $\mu$ m [14]. Meanwhile, the Codex Alimentarius Commission state that particles in the smoke had the size of 0.2-0.4  $\mu$ m generally or as low as 0.05 to 1  $\mu$ m, and estimated to constitute 90% of its overall weight [2]. In addition, smoke produced from biomass combustion contains components of char, ash, soot and tar fraction. Tar according to Sreelal (2015) is a by-product of a combustion process that commonly produced by a gasifier. This by-product is formed when the mass of wood or other biomass material is converted into flammable gases with some ash and charcoal residue. Tar could be in the form of a liquid, and mixed with flammable gases include methane (and other simple gaseous hydrocarbons), hydrogen and carbon monoxide [31]. All forms of the solid particles have commonly become a contaminant in processed fish, especially for forced convection smokehouse. Several methods such as settling chamber, cyclone separator, liquid scrubbers, filters and electrostatic precipitators can be used to overcome the contaminating solid particles in the smoking process [4]. Settling chamber is probably the simplest and the earliest type while cyclone separator is one of the most widely used in dust-collection equipment [22].

The biomass material burned in this study to generate smoke was coconut shell. The coconut shell was chosen because of its relatively high heating value. The high heating value was required to achieve temperature generally used in the hot smoking method. The coconut shell also contains higher combustible matter and lower ash content than other biomass such as rice straw and sugarcane bagasse [32].

Solid particles resulted from biomass burning mostly fly ash can become a contaminant in the fish smoking process unless they are handled appropriately. The fly ash from biomass burning is also recognised as a major source of ultrafine particles that can cause undesirable effects when inhaled. These effects can include cardiovascular and pulmonary diseases as well as lung cancer [15, 23]. The results reported in the literature show that the size of biomass fly ash particles varies from



 $0.01-0.05 \ \mu\text{m}$  up to more than 1-2 mm, but these materials are usually excellent as their median size, which dominant below 10 - 100  $\mu\text{m}$  [18, 35]. Particle density of biomass ash varies between about 2180 and 2750 kg/m<sup>3</sup> [11], and up to 3021 kg/m<sup>3</sup> [35]. The values of particle density indicated previously are for ash particles from the combustions of wheat straw and wood kinds. A lower value of particle density is found on ash particle from coconut shell (2050 kg/m<sup>3</sup>) [16]. The bulk density of biomass fly ash were mostly between 101 - 830 kg/m<sup>3</sup> (mean 392 kg/m<sup>3</sup>) [9, 35], and up to 960 kg/m<sup>3</sup> [34].

Design aspects of a smokehouse evolved from traditional to a modern system that presents novelties such as of directly smoking or indirectly, natural or forced air circulation and structural design of smoking chamber and smoke box separately or non-separated. There is not a milestone to indicate when the innovation of smokehouse has been begun, but there have been modifications of design system since 1939. The Torry kiln smokehouse (Scotland) known as the first smoking device in smoking history and brought a revolution in the industry of fishing [39]. Since that, the design of the smokehouse was developed in various models according to local custom. In Ghana, modifications of the fish smoking oven with innovation are the oven types introduced by Adjetey (1962) and Chorkor (1970) [7]. The oven type of Adjetey had the separate smoke box and smoke chamber, chimney, and fish travs. Meanwhile, the Chorkor type had good smoking conditions, used traditional materials, easy handling (trays), fuel efficiency and healthier operation. Other types of the fish smoking kiln are those from Nigeria, Ghana, and Indonesia. The fish-smoking kiln designed in Nigeria had three layers; stainless steel, glass fibre as insulation and mild steel for the peripheral walls. The design was addressed to make enclosed kiln to uniformly smoked fish under hot smoking temperature or above (120-200 °C) from sawdust and maize cob as fuels [20]. In a recent modification from Ghana, the traditional oven was equipped with a removable filter filled with activated charcoal to reduce PAH contamination. This system used natural-air circulation with the wood burning chamber and the smoking chamber separated by a removable filter [5]. The oven type from Indonesia is a smoking cabinet with a vertical array of trays. In this system, the smoke box is set up at the bottom with upward natural-air circulation. The smoking chamber and the smoke box are separated only by a wire mesh [24].

Among the smokehouses described previously, none has been designed to overcome residuals of biomass burning (char, ash, dust, soot, and tar), especially for the forced smoke-air stream smokehouse. Hence, it is important to design an indirect smoking, which separates the smoking chamber from the biomass-burning chamber with a device to separate contaminants from biomassburning residuals. The objective of this study was to design and test the performance of an integrated cyclone separator with a heat exchanger as the smoke-heat generator. The cyclone separator designed in this study was equipped with a centrifugal blower intended to separate solid particles from the smoke-air stream. Meanwhile, the shell structure with baffles of the heat exchanger aims to hold up the tar and fine fraction of ash or dust that pass through the cyclone.

#### MATERIALS AND METHODS

#### **Cyclone separator**

The cyclone separator was designed according to high-efficiency Stairmand's cyclone. The scale of cyclone dimension is as Table-1.

Cyclone geometry	Scale
(1)	(2)
Diameter (D)	D
Height of inlet (a)	0,5*D
Width of inlet (b)	0,25*D
Diameter of outlet (do)	0,5*D
Diameter of dust outlet (Bc)	0,375*D
Length of cyclone body (h)	1,5*D
Length of cyclone cone (hc)	2,5*D
Total length (H)	4*D

**Table-1.** Dimension of the cyclone.

The standard design for high-efficiency cyclone have characteristics; 0.203 m in diameter, flow rate (Q<sub>1</sub>) 223 m<sup>3</sup>/h, solid-fluid density difference ( $\Delta \rho_1$ ) 2000 kg/m<sup>3</sup> and test fluid viscosity air at 1 atm, 20 °C ( $\mu_1$ ) 1.81x10<sup>-5</sup> N.s/m<sup>2</sup>.

The design of cyclone is assumed to operate on temperature approximation of 100 °C (fluid viscosity,  $\mu_2 =$  $2.1 \times 10^{-5}$  N.s/m<sup>2</sup>), solid-fluid density difference is equal to  $(\Delta \rho_2)$  2050 kg/m<sup>3</sup>. The centrifugal blower with flow rate 282 m<sup>3</sup>/h and static pressure of 0.65 kPa will drive the cyclone separator. It is recommended the minimum gas velocity for the conveying velocities in the pipe that are dependent upon the nature of the contaminant. Gas velocities for the contaminant close to the smoke/fumes/very light dust were about 10 m/s, 15 m/s for dry medium density dust (sawdust, grain) and 25 m/s for heavy dust (metal turnings) [10].

In addition, the design of cyclone separator was also based on the particle size distribution of ash/dust from the wall of the chimney as presented in Table-2 column (1) and (2). In the same Table-2 on column (3) and (4), particle size distribution from cyclone separator testing is presented as materials to be analyzed. The particle size distributions of both sources are presented in Table-2.

Particles size, µm	Pre-design, % weight less than	Particles size, µm	After-design, % weight less than
(1)	(2)	(3)	(4)
50	84.83	80	73.54
40	73.49	56	52.12
28	54.17	38	33.92
20	37.44	20	18.57
10	13.85	10	9.02
5	5.21	5	4.56
2	1.61	2	1.6

The calculation and conversion use technical equation (1) - (2) below:

$$A_i = \frac{Q_{blower}}{V_i} \tag{1}$$

$$a*b = 0.5D*0.25D = 0.125D^2 = A_i$$
 (2)

Then the diameter of the cyclone was found, D = 0.25 m and the entire cyclone dimension in scale as in Table-1. We could predict the efficiency of the cyclone separator design based on particles that had been brushed from the chimney. The prediction of efficiency was also based on performance curve of the high-efficiency cyclone. As we note C1 and C2 is a subscript for cyclone separator standard and cyclone separator designed respectively, the following equation (3) is used to transform and obtain scaling factor (d<sub>2</sub>) [30].

$$d_{2} = \left[ \left( \frac{D_{C2}}{D_{C1}} \right)^{3} * \frac{Q_{1}}{Q_{2}} * \frac{\Delta \rho_{1}}{\Delta \rho_{2}} * \frac{\mu_{2}}{\mu_{1}} \right]^{1/2}$$
(3)

On this step,  $d_2$  was found for about 1.345 and used to transform the mean particle size from Table-2 on the pre-design column. Transformation of  $d_2$  is shown in Table-3, column (3) to yield the scaled mean particle or the mean particle of the column (1) divided by  $d_2$ .

Pa. Size µm	Percentage in range	Mean Pa. Size, µm	ηi (%)	Collected,% (2)*(4)/100
(1)	(2)	(3)	(4)	(5)
>50	15.17	37.18	98.5	14.94
40-50	11.34	33.46	97.8	11.09
28-40	19.32	25.28	97.0	18.74
20-28	16.73	17.85	95.5	15.98
10-20	23.59	11.15	93.0	21.94
05-10	8.64	5.58	88.5	7.65
02-05	3.60	2.60	72.5	2.61
0-02	<u>1.61</u>	0.74	25.0	0.40
	100			93.3

Table-3. Prediction of overall collected efficiency.

The pressure drop of the cyclone separator designed is also important to be observed. It will give information of blower specification to be applied and the satisfactory operation. The pressure drop of the cyclone separator designed is calculated using equation (4):

$$\Delta P = \frac{\rho_g}{203} \left\{ v_i^2 \left[ 1 + 2\phi^2 \left( \frac{2r_t}{r_e} - 1 \right) \right] + 2v_o^2 \right\}$$
(4)

Where  $\phi$  is taken from the cyclone pressure drop factor [31] and the value of pressure drop for the predesign prediction was about 332 Pa.

The particles that enter to the cyclone separator will be collected with 50% efficiency. The equation (5) and equation (6) developed by Lapple [12] is used to calculate the 50% cut diameter of the particle  $(d_{pc})$  and the collection efficiency by equation (7), [20].

$$d_{pc} = \left[\frac{9\mu_2 b}{2\pi N_e v_i (\rho_p - \rho_g)}\right]^{1/2}$$
(5)

Where Ne is the number of airflow revolution:

$$N_e = \frac{1}{a} \left[ h + \frac{H - h}{2} \right] \tag{6}$$

Finally, the collection efficiency of any size of particles given by:

$$\eta_i = \frac{1}{1 + (d_{pc}/\bar{d}_{pi})^2} \tag{7}$$

Another analysis is for the PAH, benzo(a)pyrene compound (a PAH characteristic) contained in the smoked fish product was done by high-performance liquid chromatography (HPLC) method. HPLC is one method

that very suitable for the determination of PAH in a variety of smoked meat products [28, 29]. In the experiment, this method used in triplo samples with a limit of detection (LOD)  $0.25 \mu g/kg$ .

#### **Experimental setup**

The design of cyclone separator has dimensions as Table-4. The Dimensions of the cyclone separator are given as scales in Table-1 and the initial value of cyclone diameter is given in equation (1) - (2).

Table-4. Dimensions of cyclone separator.

Cyclone geometry	<b>Dimension</b> (m)
(1)	(2)
Diameter (D)	0.25
Height of inlet (a)	0,125
Width of inlet (b)	0,0625
Diameter of outlet (do)	0,125
Diameter of dust outlet (Bc)	0,09375
Length of cyclone body (h)	0,375
Length of cyclone cone (hc)	0.625
Total length (H)	1

An integrated cyclone separator with heat exchanger was developed at the mechanisation and agricultural equipment laboratory of Politeknik Gorontalo (Indonesia). The schematic diagram of that integration, as a unity of the smoke-heat generator, is shown in Figure-1.



**Figure-1.** The smoke-heat generator, schema (a): (1) Furnace, (2) heat exchanger, (3) blower, (4) cyclone separator, (5) dustbin, (6) smoke outlet. Schema (b): (7) biomass feeder, (8) air/burning residue duct, and ( $\Delta P$ ) pressure drop of inlet/outlet cyclone with 5° angle at inlet cyclone.

The performance of particles separation by the cyclone had already been tested and the particle size distributions are presented in Table-2, on the after-design column. These particles have a broader range of 0.2 - 600 µm. Calculation of the overall collection efficiency of particles separation uses equation (5) - (7) and it is shown in Table-5.

Pa. Size (µm)	Percentage in range	Mean Pa. Size, µm	ηi (%)	Collected,% (2)*(4)/100		
(1)	(2)	(3)	(4)	(5)		
>80	26.46	80.0	99.8	26.40		
56-80	21.42	68.0	99.7	21.35		
38-56	18.20	47.0	99.3	18.07		
20-38	15.35	29.0	98.2	15.07		
10-20	9.55	15.0	93.5	8.93		
05-10	4.46	7.5	78.4	3.49		
02-05	2.96	3.5	44.1	1.30		
0-02	<u>1.60</u>	1.0	6.0	<u>0.10</u>		
	100			94.7		

Table-5. Overall collected efficiency.

The total pressure drop is calculated both the static pressure and the dynamic pressure for the cyclone inlet and outlet. The static pressure drop  $(P_{is} - P_{os})$  of the cyclone inlet and outlet were measured by Hiyoshi model AP110. While the dynamic pressure drop  $(P_{id} - P_{od})$  of the cyclone inlet and outlet were calculated by equations. The total pressure drop equation was adapted from Zhu *et al.* [40] as equation (8) below:

$$\Delta P = (P_{is} + P_{id}) - (P_{os} + P_{od}) \tag{8}$$

The dynamic pressure  $(P_d)$  of inlet and outlet were calculated under each condition according to the equation (9):

$$P_d = \rho_g \frac{v^2}{2} \tag{9}$$

The value of static pressure drop  $(P_{is} - P_{os})$  and dynamic pressure drop  $(P_{id} - P_{od})$  was 176 Pa and 28 Pa respectively.

#### **RESULTS AND DISCUSSIONS**

#### **Cyclone efficiency**

The collection efficiency and pressure drop of the cyclone separator are the major analyses to be done in this work. As a design process, there are sets of data and calculations used to result in a real dimension of the cyclone separator (pre-design). Cyclone separator designed in this work was based on the particle size distribution of ash brushed from the wall of a chimney, where the husk and coconut shell were burned down at the bottom. The smallest size of the particle as analysed by CILAS 1190 LIQUID was 0.2  $\mu$ m with the amount of percentage (by weight less than 2  $\mu$ m) was 1.61% (Table-2). While the largest size of the particle was 112  $\mu$ m, thus the range size of the particle from the chimney was 0.2 – 112  $\mu$ m. The pre-design of the cyclone separator was also

based on the calculations of high-efficiency Stairmand's cyclone including the set of data used from the standard design. In the pre-design, calculation of the overall collection efficiency as shown in Table-3 was 93.3%. This value satisfied the design of the cyclone according to the performance curves [30]. The design of the cyclone was also safe since the overall collection efficiency was more than 90%, which at least as the conventional type [6, 25, 38]. Meanwhile, the pressure drop of the cyclone separator as a prediction in the pre-design was about 332 Pa.

The particle size distribution of ash/dust analysed by CILAS instrument for separation performance of the cvclone designed had a more width range of 0.2 - 600 um. In regards to similarity with the particle previously, both sources had the smallest particle size of 0.2 µm but slightly different in the amount of percentage (by weight less than 2  $\mu$ m) equal to 1.6% (Table-2). The collection efficiency of the designed cyclone was 94.7 % (Table-5). This value has exceeded the prediction of 93.3 % although it was not too far, that it could be concluded to be valid. There are two types of cyclone separator related to the level of collection efficiency; more than 90% for conventional type and more than 90-95% for enhanced type. In the conventional type, the energy required is low with pressure drop in moderate to high (7.5-27.5 kPa) and categorised in very high flow capacity [38] adapted from Seville [25].

Commonly, description of the separation performance of the cyclone can be seen in Figure-2(a). In this graph, the grade of collection efficiency for particle diameter below 10  $\mu$ m was only 78.4% of the highest, conversely, as much as 21.6% assumed to be passing through the cyclone separator.





Figure-2. (a) Collection efficiency of any size particles, (b) Trendline of efficiency & cut-off diameter based particle density.

The particle of ash or dust that sized 0.2 µm was the smallest size, to be evidence either in the pre-design cyclone or in the after-design cyclone. As the number of these particles classified by weight less than 2 µm was 1.61% in pre-design and 1.6% in after-design, it could be stated that only 0.01% of particle that passes through the cyclone separator. In the same case were for particles classified by weight less than 5 µm and 10 µm whose difference of 0.65% and 4.83% respectively. On this view, the separation performance of particles size below 10 µm could reach over 90%, as seen as on the surface of the smoked fish product that very clean (visual observation). This fact was another perception of the separation performance according to the occurrence of the particle from the combustion of coconut shell. It is noted that the data on after-design was not a result of testing series with the data in pre-design.

The cut-off particle size diameter  $(d_{50})$  was another performance indicator of a cyclone. It could be defined as a 50 percent of the particles size that was separated into the dustbin. Particles which were larger than d<sub>50</sub> were more likely to be separated, on the contrary, particles which smaller than d<sub>50</sub> was more liable to pass through the outlet of the cyclone. The cut-off particle diameter as Figure-2(a) for particle density of 2050 kg/m<sup>3</sup> with collection efficiency of 94.7 % was 3.94 µm, also shown in Figure-2(b). The collection efficiency was the main consideration in the choice of the cyclone separator practical application. However, the collection for efficiency of the cyclone varied with particle size, shape and density, the fluid throughput and the geometry of the cyclone [9]. In the Figure-2(b), it shows an increasing grade of collection efficiency for particle density in the range of 1500 - 2800 kg/m<sup>3</sup>. It also illustrates the cut-off particle size which moved from about 4.6 to 3.4 µm for the same range of the particle density. Thus, these performances imply the different character of the cyclone separator for a different kind of biomass burning in the furnace. Solid-fluid density difference of the cyclone designed in this calculation was 2050 kg/m<sup>3</sup>, which was



taken from particle density of fly ash from coconut shell [16]. This value was chosen for at least two reasons. One is because of the same fuel of coconut shell that was burned in the furnace of the experiment. Another reason is the value which was lower than the fly ash particle of wood chip 2570 kg/m<sup>3</sup> with bulk density 660 kg/m<sup>3</sup> [11]. The bulk density of ash particle from the experiment of this cyclone separator was also lower, namely 521 kg/m<sup>3</sup>.

#### Cyclone pressure drop

The pressure drop of the cyclone separator is an indicator for energy consumption level. The higher the pressure drop of a cyclone separator, the higher the energy consumed. The total pressure drop which was measured and calculated from equation (9) result in a value of about 204 Pa. The static pressure measurement of inlet and outlet of the gas stream was done nearly at ambient temperatures in which the ash particle possibility was loaded very slightly. The component of this static pressure and dynamic pressure of the cyclone was 176 Pa and 28 Pa respectively. This value was lower than the pressure drop that was predicted from equation (4) equal to 332 Pa. In the operational testing for fish smoking of 11.6 hours, the consumed energy was 1.28 kWh or equal to 4.6 MJ. The ratio of the consumed energy to the pressure drop of the cyclone separator was 22.6 MJ/Pa.

#### Solid particles

The particle size distributions by CILAS instrument that were done for fly ash particles from the chimney and those of collected in the dustbin were both similar in the smallest size. It was explained that the ash or dust particles, which were flying with smoke-air within cyclone, had the same characteristic as the fly ash particles brushed from the chimney. On the contrary, the differences between both sources of ash particles were in their ranges. The ash particles collected in the dustbin as a part of cyclone performance were wider than the ash brushed from the wall of the chimney. The ash particles from chimney were in the range only from  $0.2 - 112 \mu m$ . It seems that the ash fraction was only influenced by the updraft forces of heat burning. On the one hand, the ash particles collected in the dustbin were influenced by centrifugal forces of the blower. Thus, the range was wider from 0.2 to 600  $\mu$ m, which could be like other contaminants such as fine-fraction of charcoal and sand. In comparison with the size of smoke particles, the range of ash or dust particles that separated by the cyclone was overlapped. Generally, particles of the smoke had sizes from 0.2 to 0.4 µm or as low as from 0.05 to 1 µm. So there was overlap in the range of 0.2 - 1 µm that affected the cleanliness of the smoke. The ash or dust particle with the average size of 1 µm as seen in Table-5 had a collecting efficiency by 6.0 %. The separation performance of this particle size also affects the smoke healthier from the fraction of tar. The residual of biomass burning could be in form of ash, char, and fraction either carbon black (soot) or tar that potentially harms the human health through smoked food. The carbon blacks were

material considered as substances that potentially contaminated with carcinogenic aromatic hydrocarbons since certain of them had been shown to contain 3,4-benzpyrene [21, 37]. Carcinogenic hydrocarbon was also found in the food because of the smoking process. It was in much higher concentrations for smoked food that occasionally from contamination by soot [37].

#### Smoke, tar, and fine particles

Tars in some references are a complex mixture of organic compounds (including aromatic and heteroaromatic species as well as polycyclic aromatic hydrocarbon compounds PAHs) which condense at room temperature [14, 17]. Tar Formation according to empirical models, can be occurred either in low temperatures or in higher temperatures [36], in higher temperatures (300-500 °C) the molecule was rapidly depolymerized which further react to provide substance with tar component. At the temperature of 300 °C, the production level of tar had achieved 60% from cellulose under vacuum condition [26].

A specific discussion addressed to the fraction of tar mixed with smoke (fume/favour) and fine particles (smaller than the cut-off diameter), which were more likely to pass through the cyclone separator. On the smoke-heat generator design, there was a heat exchanger where the cyclone separator integrated between the bundle of tubes and shell structure with baffles. The travel of smoke with tar component in the bundle of tubes occurred with the effect of decreased temperature. The decreasing of temperature affects the tar to be condensate more easily. Furthermore, the centrifugal forces of blower caused more effects to the condensation process which, in fact, made the tar was spread and sticky to the surface inside the cyclone and also in the dustbin made of glass as seen in the Figure-3(a).





**Figure-3.** (a) Tar in the dustbin, (b) A cloth of masker blackening by the smoke-fine particle at the smoke outlet, (c) Appearance of the smoked fish.

ARPN Journal of Engineering and Applied Sciences ©2006-2017 Asian Research Publishing Network (ARPN). All rights reserved.

### ISSN 1819-6608



#### www.arpnjournals.com

The smoke with tar component and the fine fraction of ash particle smaller than d<sub>50</sub> would pass through the cyclone via the outlet. The next barrier to them was the shell structure with baffles of the heat exchanger. On the shell structure that filled up with the criss-cross of tubes for one baffle, the smoke mixes tar and the fine fraction of ash particle would be turned around as much as five times. The baffles that applied as the smoke barrier to decrease PAH compound within tar was also accordingly with the recommendation of the Codex Alimentarius Commission [2]. Figure-3(b), a cloth of mask placed at the smoke outlet tried to catch the fine particle, but it was hard to analyse as only the black image found on it. While the Figure-3(c) shows a yellow-brown colour from the fish skin and clean as a smoked fish product. Thus, the fish which was processed with this new indirect smokehouse design could be diminished the PAH (benzo(a)pyrene) contamination under the Turkish Codex's maximum limit of 2.0 µg/kg, and also below the European Commission (EC) limit of 5.0 µg/kg [3, 33]. The level of benzo(a)pyrene analysed by HPLC method for fish smoked product in the experiment was 1.29 µg/kg.

VOL. 12, NO. 19, OCTOBER 2017

#### CONCLUSIONS

The cyclone separator designed in this study had the overall collection efficiency by 94.7 %, which exceeded the prediction of 93.3 %. This efficiency level has satisfied the reference curve of performance and safe since the value exceeds 90%. The particle size distribution, either the ash particles from chimney or ash/dust particle separated by the cyclone, had the same smallest size of 0.2 µm, which was overlapping with the smoke particles size. The overlapping size of particles between ash and smoke indicated that separation of the ash/dust from smoke-air stream occurred from the smallest size to the larger with the increase of collection efficiency. In addition, the particles of ash or dust and tar fraction contained in the smoke were separated and sticky within cyclone, dustbin and the structure of heat exchanger. These performances were implicated to the smoke cleanliness and made it healthier for the fish smoking process. The content of benzo(a) pyrene as a characteristic of PAH compound in the smoked fish product was 1.29 µg/kg, which was the low level and safe to consume. Pressure drop as an indicator of energy consumption showed a lower value than that of the prediction and it had a ratio of energy consumption to the pressure drop of the cyclone about 22.6 MJ/Pa. This is to say that by the performance of efficiency, the smoke health that impact to low benzo(a) pyrene, and the pressure drop, it indicates that the designed cyclone is safe for practical purposes.

#### ACKNOWLEDGEMENT

I am thankful to the RISTEK DIKTI for the integral scholarship on my postgraduate program.

#### Nomenclatures

a Height of inlet, m									
$A_i$ Cross section area of inlet, m <sup>2</sup>									
As Surf. area of cyc. exposed to the spinning fluid	Surf. area of cyc. exposed to the spinning fluid,								
b $m^2$	m <sup>2</sup>								
Bc Width of inlet, m	Width of inlet, m								
C1 Diameter of dust outlet, m	Diameter of dust outlet, m								
C2 Standard cyclone	Standard cyclone								
d <sub>2</sub> Designed cyclone	Designed cyclone								
d <sub>pc</sub> Scaling factor									
$d_{pi}$ Cut particle dia. collected with 50%	2								
D efficiency, μm									
do Diameter of particle, µm									
fc Diameter of cyclone, m									
h Diameter of outlet, m									
hc friction factor, taken as 0.005 for gases									
H Length of cyclone body, m									
N <sub>e</sub> Length of cyclone cone, m									
$\Delta P$ Total length of cyclone, m									
P <sub>s</sub> Number of airflow revolution									
P <sub>d</sub> Total pressure drop, Pa									
Q <sub>1</sub> Static pressure drop, Pa	Static pressure drop, Pa								
$Q_2$ Dynamic pressure drop, Pa	Dynamic pressure drop, Pa Standard volumetric flow rate $m^{3}/h$								
v Standard volumetric flow rate, m <sup>3</sup> /h									
v <sub>i</sub> Designed volumetric flow rate, m <sup>-</sup> /h									
$v_o$ Velocity, m/s	velocity, m/s								
$\phi$ Inlet velocity, m/s	Iniet velocity, m/s								
$\eta$ Outlet velocity, m/s	Outlet velocity, m/s								
$\eta_i$ Cyclone pressure drop factor	Cyclone pressure drop factor								
$\mu_1$ Efficiency of cyclone, %	Efficiency of cyclone, %								
$\mu_2$ Efficiency of collection of any size particles, %	Efficiency of collection of any size particles, $\%$								
$\rho_{\rm g}$ [lest gas viscosity, N.s/m]									
$\rho_p$ Cas density is $l_{rs}/m^3$									
$\Delta \rho_1$ Derticle density, kg/m <sup>3</sup>									
$\Delta \rho_2$ Solid fluid density diff in stand conditions									
$k_{\alpha}/m^3$	,								
Solid-fluid density diff of designed evelope									
kg/m <sup>3</sup>	,								

#### REFERENCES

- Ahmad J.I. 2003. Smoked Foods: Applications of Smoking, in Encyclopedia of Food Sciences and Nutrition (2<sup>nd</sup> Ed.). Academic Press, Oxford.
- [2] Codex Alimentarius Commission, CAC. 2009. Code of practice for the reduction of contamination of food with polycyclic aromatic hydrocarbons (PAH) from smoking and direct drying processes (CAC/RCP 68-2009 Adopted 2009, Revised 2009) Prevention and reduction of food and feed contamination (1<sup>st</sup>ed.). Viale delle Terme di Caracalla, Rome: Joint FAO/WHO Food Standards Programme.
- [3] EC. 2005. Commission Regulation (EC) No. 208/2005 amending Regulation (EC) No. 466/2001 as

regards polycyclic aromatic hydrocarbons. Official Journal of the European Union L/34 3-5.

- [4] Elsayed K. 2011. Analysis and Optimization of Cyclone Separators Geometry Using RANS and LES Methodologies. Ph.D. Thesis. Vrije Universiteit Brussel. Brussel.
- [5] Essumang D.K., Dodoo D.K. and Adjei J.K. 2014. Effective reduction of PAH contamination in smoke cured fish products using charcoal filters in a modified traditional kiln. Food Control. 35, 85-93.
- [6] Gopani N. and Bhargava A. 2011. Design of High Efficiency Cyclone for Tiny Cement Industry. International Journal of Environmental Science and Development. 2, 350-354.
- [7] Hall G.M. and Köse S. 2014. Fish Processing Installations: Sustainable Operation, in: Boziaris, I.S. (Ed.), Seafood Processing. John Wiley & Sons, Ltd.
- [8] Ingham D.B. and Ma L. 2002. Predicting the performance of air cyclones. International Journal of Energy Research. 26, 633-652.
- [9] James A.K., Thring R.W., Helle S. and Ghuman H.S. 2012. Ash Management Review. Applications of Biomass Bottom Ash. Energies. 5, 3856-3873.
- [10] Kaupp A. and Goss J.R. 1984. Small Scale Gas Producer-Engine Systems. Friedr. Vieweg & Sohn, Braunschweig/Wiesbaden.
- [11] Lanzerstorfer C. 2015. Chemical composition and physical properties of filter fly ashes from eight gratefired biomass combustion plants. Journal of Environmental Sciences. 30, 191-197.
- [12] Lapple C.E. 1951. Processes Use Many Collector Types. Chemical Engineering. 58.
- [13] Lea-Langton A.R., Baeza-Romero M.T., Boman G.V., Brooks B., Wilson A.J.M., Atika F., Bartle K.D., Jones J.M. and Williams A. 2015. A study of smoke formation from wood combustion. Fuel Processing Technology. 137, 327-332.
- [14] Li C. and Suzuki K. 2009. Tar property, analysis, reforming mechanism and model for biomass gasification-An overview. Renewable and Sustainable Energy Reviews. 13, 594-604.
- [15] Longhin E., Gualtieri M., Capasso L., Bengalli R., Mollerup S., Holme J.A., Øvrevik J., Casadei S., Di

Benedetto C., Parenti P. and Camatini M. 2016. Physico-chemical properties and biological effects of diesel and biomass particles. Environmental Pollution. 215, 366-375.

- [16] Madakson P.B., Yawas D.S. and Apasi A. 2012. Characterization of coconut shell ash for potential utilization in metal matrix composites for automotive applications. International journal of engineering science and technology. 4, 1190-1198.
- [17] Milne T.A. and Abatzoglou N. 1998. Biomass Gasifier "Tars": Their Nature, Formation, and Conversion. Retrieved February, 18 2017, from http://www.nrel.gov.
- [18] Mylläri F., Karjalainen P., Taipale R., Aalto P., Häyrinen A., Rautiainen J., Pirjola L., Hillamo R., Keskinen J. and Rönkkö T. 2017. Physical and chemical characteristics of flue-gas particles in a large pulverized fuel-fired power plant boiler during cocombustion of coal and wood pellets. Combustion and Flame. 176, 554-566.
- [19] Overcamp T.J. and Mantha S.V. 1998. A simple method for estimating cyclone efficiency. Journal of Environmental Progress. 17, 77-79.
- [20] Oyerinde A.S., Ogunlowo A.S. and Olukunle O.J. 2013. Development of a Cross-Flow Fish Smoking Kiln Fired by Biomass Material. Journal of Agricultural Science and Technology A. 531-541.
- [21] Pence B.C. and Buddingh F. 1987. Co-carcinogenic effect of carbon black ingestion with dietary fat on the development of colon tumors in rats. Toxicology Letters. 37, 177-182.
- [22] Perry R.H. and Green D.W. 1997. Perry's Chemical Engineers' Handbook. McGraw-Hill, 1997, 7<sup>th</sup> ed. ed. McGraw-Hill.
- [23] Pope C.A., Dockery D.W. and Schwartz J. 1995. Review of epidemiological evidence of health-effects of particulate air-pollution. Inhalation Toxicology. 7(1) 1-18.
- [24] Royani D.S. 2015. Engineering Tool of Cabinet Type Smoking Fish, (in Indonesian). Jurnal Aplikasi Teknologi Pangan. 4, 74-78.
- [25] Seville J.P.K. and Clift R. 1997. Gas Cleaning in Demanding Applications (1<sup>st</sup>ed). Springer Netherlands.

- [26] Shafizadeh F. 1982. Introduction to pyrolysis of biomass. Journal of Analytical and Applied Pyrolysis. 3, 283-305.
- [27] Sikorski Z.E. and Sinkiewicz I. 2014. SMOKING | Traditional, in: Encyclopedia of Meat Sciences (2<sup>nd</sup> Ed.). Academic Press, Oxford.
- [28] Simko P., Dubravicky J. and Smirnov V. 1989. Effect of smoking technology on the contents of benzo(α)pyrene in cured meat products. Potravinářské vědy. 7, 59-63.
- [29] Simko P. 1991. Changes of benzo(a)pyrene contents in smoked fish during storage. Food Chemistry. 40, 293-300.
- [30] Sinnott R.K. 2005. Chemical Engineering Design (4<sup>th</sup>Ed). Elsevier Butterworth-Heinemann.
- [31] Sreelal G. 2015. Design, Construction & Performance Analysis of Low Cost Fixed Bed Biomass Gasifier. ARPN Journal of Engineering and Applied Sciences. 10, 2736-2742.
- [32] Tsai W.T., Lee M.K. and Chang Y.M. 2006. Fast pyrolysis of rice straw, sugarcane bagasse and coconut shell in an induction-heating reactor. Journal of Analytical and Applied Pyrolysis. 76, 230-237.
- [33] Turkish Food Codex. 2008. Turkish food codex communiqué on determining the maximum levels of certain contaminants in foodstuffs. The Official Gazette. 17.05.2008/26879.
- [34] Van Alkemade I., Loo S. and Sulilatu W. 1999. Exploratory Investigations into the Possibilities of Processing Ash Produced in the Combustion of Reject Wood. Retrieved February 4, 2017, from http://www.ieabcc.nl.
- [35] Vassilev S.V., Baxter D., Andersen L.K. and Vassileva C.G. 2013. An overview of the composition and application of biomass ash. Part 2. Potential utilization, technological and ecological advantages and challenges. Journal of Fuel. 105, 19-39.
- [36] Waheed Q.M.K., Nahil M.A. and Williams P.T. 2013. Pyrolysis of waste biomass: investigation of fast pyrolysis and slow pyrolysis process conditions on product yield and gas composition. Journal of the Energy Institute. 86, 233-241.

- [37] WHO. 1961. Evaluation of the carcinogenic hazards of food additives. Technical Report Series N0.220. Geneva.
- [38] Woolcock P.J. and Brown R.C. 2013. A review of cleaning technologies for biomass-derived syngas. Journal of Biomass and Bioenergy. 52, 54-84.
- [39] www.grillsforever.com. 2016. Torry Kiln Smokehouse: The First Smoking Device in Smoking History.
- [40] Zhu Y., Kim M.C., Lee K.W., Park Y.O. and Kuhlman, M.R. 2001. Design and Performance Evaluation of a Novel Double Cyclone. Journal of Aerosol Science and Technology. 34, 373-380.